

## **NOTES:**

- 1. AIR RELEASE RISER AND PVC PIPE HOUSING SHALL BE PLACED AND MAINTAINED IN VERTICAL POSITION.
- 2. METALLIC THREADS TO BE COATED WITH BITUMASTIC COATING.
- 3. INSTALL TAPPING SADDLE FOR THICKNESS CLASS D.I. MAINS 4" & SMALLER, PRESSURE CLASS D.I. MAINS 8" & SMALLER, OR WHEN MAIN IS PVC, HDPE, OR AC PIPE.
- 4. FOR MANHOLE/VALVE BOX IN GRASS AREAS, SEE SS 21.0 SHEET 1 OF 1.

ITEM	CROSS REF.	SPEC. REF.
TYPE A MANHOLE	55 4.0	

	L	
MIAMI-DADE		
COUNTY	L	
Delivering Excellence Every Day		
WATER & SEWER DEPARTMENT	r	
WHEN & SENER DEFAINMENT	L	

<u>ISSUE DATE</u>	<u>APPROVED BY</u>
6/29/2011	F.A.

STANDARD DETAIL

AIR RELEASE VALVE ASSEMBLY
IN PAVED AREAS FOR
SEWAGE FORCE MAINS

SS 11.0 SHEET 1 OF 2